

# **3800** SERIES

SINGLE STAGE END SUCTION PUMPS

MODEL 3804

MODEL 3801

MODEL **3801** Close-Coupled End Suction Pumps

MODEL **3804** Flexible-Coupled End Suction Pumps

#### pentair.com/aurora

## **HIGH-PERFORMANCE PUMPING**

Equipped with shared hydraulics, premium materials, and optimized design features, Pentair Aurora<sup>®</sup> 3800 Series pumps are designed to meet modern compliance requirements while delivering next-level performance.



Contact us to learn more about our NSF certified products.





### **3800** SERIES Single Stage End Suction Pumps

Applications	Max Flow	Max Head	Max Temp	Stages	Coupling	Configurations	Certifications	
Municipal/Industrial/ Commercial: • HVAC	<b>4,200 gpm</b> (954 m <sup>3</sup> /hr)	<b>520 ft</b> (158 m)	<b>275° F</b> (135° C)	Single	Close (3801)	Horizontal	NSF372 NSF61 NSF50	
<ul><li>Boosting</li><li>Hot/cold water</li></ul>					Flexible (3804)			

#### **FLEXIBLE**

- Double volute discharge helps reduce bearing loads<sup>1</sup>
- Back pullout casing feet make service easy
- Gauge taps on suction and discharge flanges boost visibility
- Optional seal materials match largest installed base flange to flange<sup>2</sup>

#### DURABLE

- Ductile iron casings allow for higher working pressures
- Carbon mechanical seal built with durable 303 stainless steel metal parts and Buna-N $^{\odot}$  flexible elastomers
- Stainless steel shaft sleeve protects the motor
- Stainless steel impeller is keyed and secured to the shaft extension
- Steel shaft reduces deflection<sup>2</sup>
- Re-greaseable bearings help reduce friction<sup>2</sup>

#### RELIABLE

- High-performance motors help reduce pump noise<sup>3</sup>
- Factory hydrostatic testing guarantees casing and seal integrity
- Suction splitter capabilities help reduce pre-rotation and boost efficiency
- Optional casing wear rings help reduce internal recirculation

LIFECYCLE SUPPORT FOR YOUR PUMP

• Heavy-duty power frame delivers 100,000 hours of re-greaseable bearing<sup>2</sup>

<sup>1</sup>excluding 4x5x11 and 4x5x13.5. Single volute also available <sup>2</sup>3804 only <sup>3</sup>JM + JP motors on 3801, T + TS motors on 3804

## HYDRONIC ACCESSORIES

Get the most out of your system with a wide range of hydronic accessories that can help boost performance and reliability.

Learn more at pentair.com/pumpcare

#### 800 Airport Road | North Aurora, IL, 60542 | Ph: 630.859.7000 | pentair.com/aurora

When it's time to service your pump equipment with replacement parts, there's no

room to gamble on unknown suppliers. We carry thousands of genuine OEM parts

Buna-N is the registered trademark of Pittway Corporation, Chicago.  $NSF^{\circ}$  is a registered trademark of NSF International.

tailored to Pentair pumps, ready to ship quickly.

All indicated Pentair trademarks and logos are property of Pentair. Third party registered and unregistered trademarks and logos are the property of their respective owners. © 2024 Pentair. All Rights Reserved.





MODEL 3804