

# WLCS-1000

## Dual Stage Filtration System

### FEATURES/BENEFITS

- Completely assembled with filter cartridges and quick-connect fittings for easy installation
- Effectively reduces chemicals and other contaminants from drinking water
- Includes electronic monitor for filter replacement reminders
- Compact, space saving design fits conveniently undersink
- Filter life: 12 months or 1,000 gallons (3,785 L)
- Service flow rate @ 60 psi (4.1 bar): 0.5 gpm (1.9 Lpm)



System Tested and Certified by NSF International to NSF/ANSI 42 and 53 for the reduction of the claims specified on the Performance Data Sheet.

EPA EST. 090375-MEX-001

### SPECIFICATIONS

MODEL	PART NUMBER	INLET/OUTLET	DIMENSIONS	MICRON RATING (NOMINAL) $\mu$	OPERATING PRESSURE	TEMPERATURE RANGE
WLCS-1000	152077	1/4" QC	9.18" W x 4.7" D x 12.72" H (233mm W x 119mm D x 323mm H)	0.5	30-125 psi (2.1-8.62 bar)	40-100°F (4.4-37.8 °C)

Replacement cartridge kit for WLCS-1000:  
W-250 (155584-51)



REDUCES



Lead



Mercury



Asbestos



Chlorine Taste & Odor



Sediment



VOC



Cysts

NSF/ANSI Standard 53 Certified to reduce cysts such as *Cryptosporidium* and *Giardia* by mechanical means.