

## PENTEK MICROGUARD SERIES MEMBRANE FILTER CARTRIDGE

IDEAL FOR POINT-OF-USE APPLICATIONS



**Pentair Pentek® MicroGuard Series membrane filters provide safer and cleaner drinking water without incorporating chemicals into the media or adding chemicals to the filtered water.**

**The MG-10MCB is uniquely designed with integral carbon block and sediment pre-filtration for the reduction of chlorine taste & odor and for providing extended life of the internal membrane element. This cartridge has 2.5 times greater filtration surface area than some carbon blocks, and operates at a higher flow rate with lower pressure drop. This makes the MG-10MCB ideal for Point-of-Use (POU) applications.**

### FEATURES/BENEFITS

Reduces particles as small as 0.15 micron in size by mechanical means

Combined carbon block and sediment pre-filtration for extended life and chlorine taste & odor reduction

Utilizes highly asymmetric polyethersulfone membrane with proprietary hydrophilic formulation for immediate wetting and high flow

Double O-ring endcap seals for absolute sealing in Pentair Pentek 3G housings

No electrical power required

Retains natural mineral content of water

### SPECIFICATIONS

Filter Media – Polyethersulfone

Endcaps – Top: Polystyrene

Bottom: Polypropylene

Membrane Assembly – Polystyrene, epoxy resin

Carbon Pre-filter - Activated carbon, synthetic polymeric fibers & binders

Netting – Polyethylene

O-ring Seals – EPDM

Temperature Rating – 40-140°F (4.4-60°C)

## RECOMMENDED OPERATING CONDITIONS

MODEL #	PART #	PRESSURE DIFFERENTIAL	STORAGE TEMPERATURE RANGE	pH RANGE	OPERATING PRESSURE RANGE	WATER TURBIDITY
MG-10MCB	255420-43	88 psi (6.1 bar) max	35-104° F (2.0-40° C)	2-12	5-88 psi (0.35-6.1 bar) max	<1 NTU

## SPECIFICATIONS AND PERFORMANCE

MODEL #	PART #	MAXIMUM DIMENSIONS	RATING (ABSOLUTE)*	INITIAL ΔP (PSI) @ FLOW RATE (GPM)*	ESTIMATED CAPACITIES**
MG-10MCB	255420-43	2.88" x 10.28" (73 mm x 261 mm)	0.15	11 psi @ 1 gpm (0.76 bar @ 3.8 Lpm)	200-600 gallons (757-2,271 L)

\*Based on manufacturer's internal testing.

\*\*Capacities may vary depending on local water quality, type of pre-filtration and acceptable minimum flow rate.

NOTE: Cartridge not intended for converting wastewater or raw sewage into drinking water.

WARNING: Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system.



5730 NORTH GLEN PARK ROAD, MILWAUKEE, WI 53209

P: 262.238.4400 | F: 262.238.4404

WATERPURIFICATION.PENTAIR.COM

CUSTOMER CARE: 800.279.9404 | tech-support@pentair.com

© 2017 Pentair Residential Filtration, LLC. All rights reserved.

§For a detailed list of where Pentair trademarks are registered, please visit [waterpurification.pentair.com/en-US/aboutpentair/brands/](http://waterpurification.pentair.com/en-US/aboutpentair/brands/). Pentair trademarks and logos are owned by Pentair plc or its affiliates. Third party registered and unregistered trademarks and logos are the property of their respective owners.

4003526 REV E MY17