



Thermoplastic Sump Pump

High-Output Performance

Thermoplastic construction

Resists corrosion

Zinc motor housing

Dissipates heat quickly and extends motor life

Stainless steel fasteners and hardware

Superior quality

Smooth Flow Hydraulics™

Deliver high performance for demanding applications

Tethered float switch

Operates in 14" basins or larger



Energy Efficient Design
Diseño Eficiente de la Energía
Conception rationnelle de l'énergie



**1/4 HP 3200 GPH
FPZS25T**

**1/3 HP 3600 GPH
FPZS33T**

**1/2 HP 4200 GPH
FPZS50T**

PERFORMANCE (GPH)							FLOAT SWITCH		SOLIDS HANDLING
DISCHARGE HEIGHT ABOVE PUMPING LEVEL	0'	5'	10'	15'	20'	MAX. LIFT	ON	OFF	
FPZS25T	3,200	2,700	2,160	1,500	-	20'	14"	5"	3/16"
FPZS33T	3,600	3,060	2,400	1,680	660	22'	14"	5"	3/16"
FPZS50T	4,200	3,660	3,000	2,160	960	22'	14"	5"	3/16"

MODEL	WARRANTY	UPC	CARTON DIMENSIONS	PALLET QTY.	WEIGHT
FPZS25T	1 YEAR	022315368453	8" x 6" x 12.75"	105	7.7 LBS.
FPZS33T	1 YEAR	022315368460	8" x 6" x 12.75"	105	7.7 LBS
FPZS50T	1 YEAR	022315368484	8" x 6" x 12.75"	105	10 LBS

Includes: 1 1/2" NPT discharge, 8' grounded power cord, piggyback-style switch for automatic or manual operation, detailed owner's manual

Check Valve replacement is recommended

293 Wright Street, Delavan, WI 53115

For Questions or Installation Instructions:

www.flotecwater.com 1-800-365-6832

