

CTO-10 CARTRIDGE

REPLACEMENT CARTRIDGE

CTO-10: 252-00210 (1pk)

CTO-10: 252-20110 (6pk)

Systems cartridge used in: FX-11: 160-50010
FX-21: 160-50015
SX2-21: 160-00350



APPLICATIONS

- ◆ Fountain beverages
- ◆ Water
- ◆ Coffee and tea

FEATURES • BENEFITS

- ◆ High capacity cartridge helps extend equipment life reducing maintenance frequency
- ◆ Activated carbon filtration enhances water taste and helps protect equipment against corrosive chlorine
- ◆ Gradient-density depth filtration reduces dirt, rust, and other debris as small as 5-microns to assure clean, clear water and protect solenoids, valves and other fittings against wear and plugging
- ◆ Improves the quality and consistency of hot and cold beverages
- ◆ Minimize waste by only replacing drop-in cartridges. No discarding of metal or plastic quick-change filters
- ◆ Replacement cartridge cost per gallon is less than proprietary quick-change filters
- ◆ NSF/ANSI Standard 42 Certified for the reduction of chlorine, taste & odor, and Particulate Class III when used on FX-11 and SX2-21 systems

INSTALLATION TIPS

- ◆ Insure cartridge is designed to replace the existing cartridge.
- ◆ Do not exceed cartridge specifications for temperature and pressure.
- ◆ Allow 3" clearance below system for filter cartridge removal and replacement.
- ◆ Feed-water connection to system should be COLD only.

OPERATION TIPS

- ◆ Change cartridges on a regular six (6) month preventative maintenance program.
- ◆ Change cartridges when capacity is reached or when flow becomes too slow.
- ◆ Always flush the filter cartridge at time of installation and cartridge change.

SIZING

- ◆ Service Flow Rate: 1.5 gpm (5.7 lpm)
- ◆ Rated Capacity: 15,000 gals. (56,775 L)


CTO-10 CARTRIDGE

252-00210 & 252-20110

CTO-10: 252-00210 (1pk)

CTO-10: 252-20110 (6pk)

Systems cartridge used in: FX-11: 160-50010
FX-21: 160-50015
SX2-21: 160-00350



SPECIFICATIONS

- ◆ **Service Flow Rate**
Maximum 1.5 gpm (5.7 Lpm)
- ◆ **Rated Capacity**
15,000 gallons (56,775 L)
- ◆ **Pressure Requirements**
10 – 125 psi (0.7 – 8.6 bar)
- ◆ **Temperature**
35 – 100°F (2 – 38°C)
- ◆ **Overall Dimensions**
9.8" L x 2.8" W x 2.8" D
24.8 cm x 7.11 cm x 7.11 cm
- ◆ **Electrical Connection**
None required



Tested and Certified by
NSF International against
NSF/ ANSI Standard 42:

AESTHETIC EFFECTS

Chemical Reduction
Taste & Odor
Chlorine

Mechanical Filtration
Nominal Particulate Class III
when used on FX-11 and
SX2-21 systems

The contaminants or other substances removed or reduced by this drinking water system are not necessarily in your water. Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system.

Since the conditions under which our products may be used are beyond our control, we cannot accept any liability with respect to the improper installation, application and/or use of our products.

For Pentair Everpure Product Warranties visit:
<http://pentair.com/assets/foodservice-warranty>



United States | 1040 Muirfield Drive | Hanover Park, IL 60133 | 800.942.1153 (US Only) 630.307.3000 Main | cseverpure@pentair.com | foodservice.pentair.com

Australia | 1-21 Monash Drive | Dandenong South, Vic 3175 | Australia | 011.1300 576 190 Tel | au.everpure@pentair.com

China | 21F Cloud 9 Plaza, N0 1118 | Shanghai, 200052 | China | 86.21.3211.4588 Tel | china.water@pentair.com

India | Boulevard, B-9/A, 7th Floor - Tower B Sector 62 | Noida - 201301 | 91.120.419.9444 Tel | indiacustomer@pentair.com

Europe | Pentair Water Belgium BVBA | Industriepark Wolfstee, Toekomstlaan 30, B-2200 Herentals | Belgium | +32.(0).14.283.504 Tel | sales@everpure-europe.com

Japan | Japan Inc. | Hashimoto MN Bldg. 7F, | 3-25-1 Hashimoto, Midori-ku, Sagami-hara-shi | Kanagawa 252-0143 | Japan | 81.(0)42.775.3011 Tel | info@everpure.co.jp

Southeast Asia | 390 Havelock Road, | #04-01 King's Centre | Singapore 169662 | 65.6768.5800 Tel | cseverpure@pentair.com

All indicated Pentair trademarks and logos are property of Pentair. Third party registered and unregistered trademarks and logos are the property of their respective owners.