

PTS-20 CARTRIDGE

REPLACEMENT CARTRIDGE

PTS-20: 252-00820 (1pk) PTS-20: 252-10820 (6pk)

System cartridge used in: FXTS-12 160-50004



APPLICATIONS

Ice machines

FEATURES • BENEFITS

- PolyTrix gradient-density depth filtration reduces dirt, rust, and other debris as small as 5-microns to assure clean, clear water and helps protect solenoids, valves and other fittings against wear and plugging
- Helps protect equipment from the damaging effects of scale and corrosion
- IsoNet[®]scale inhibitor helps provide consistent protection over the life of the cartridge
- NSF/ANSI Standard 42 Certified for material requirements only

INSTALLATION TIPS

- Insure cartridge is designed to replace the existing cartridge.
- Feed-water connection to system should be COLD only.
- Do not exceed system specifications for temperature and pressure.
- Allow 3" clearance below system for filter housing removal and cartridge replacement.

OPERATION TIPS


- Change cartridges on a regular six (6) month preventative maintenance program.
- Change cartridges when capacity is reached or when flow becomes too slow.
- Always flush the filter cartridge at time of installation and cartridge change.

SIZING

- Service Flow Rate: 5.0 gpm (18.9 lpm)
- Rated Capacity: N/A

PTS-20 CARTRIDGE 252-00820 & 252-10820

PTS-20: 252-00820 (1pk) PTS-20: 252-10820 (6pk) System cartridge used in: FXTS-12 160-50004



SPECIFICATIONS

- Service Flow Rate Maximum 5.0 gpm (18.9 Lpm)
- Rated Capacity N/A
- Pressure Requirements 10 - 125 psi (0.7 - 8.6 bar)
- Temperature
 35 100°F (2 38°C)
- Overall Dimensions
 20" L x 2.8" W x 2.8" D
 50.8 cm x 7.11 cm x 7.11 cm
- Electrical Connection None required



PTS-20 cartridge is Tested and Certified by NSF International against NSF/ANSI Standard 42 for material requirements only.

The contaminants or other substances removed or reduced by this drinking water system are not necessarily in your water. Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system.

Since the conditions under which our products may be used are beyond our control, we cannot accept any liability with respect to the improper installation, application and/or use of our products.

For Pentair Everpure Product Warranties visit: http://pentair.com/assets/foodservice-warranty



United States | 1040 Muirfield Drive | Hanover Park, IL 60133 | 800.942.1153 (US Only) 630.307.3000 Main | cseverpure@pentair.com | foodservice.pentair.com Australia | 1-21 Monash Drive | Dandenong South, Vic 3175 | Australia | 011.1300 576 190 Tel | au.everpure@pentair.com

China | 21F Cloud 9 Plaza, N0 1118 | Shanghai, 200052 | China | 86.21.3211.4588 Tel | china.water@pentair.com

India | Boulevard, B-9/A, 7th Floor - Tower B Sector 62 | Noida - 201301 | 91.120.419.9444 Tel | indiacustomer@pentair.com

Europe | Pentair Water Belgium BVBA | Industriepark Wolfstee, Toekomstlaan 30, B-2200 Herentals | Belgium | +32.(0).14.283.504 Tel | sales@everpure-europe.com Japan | Japan Inc. | Hashimoto MN Bldg. 7F, | 3-25-1 Hashimoto, Midori-ku, Sagamihara-shi | Kanagawa 252-0143 | Japan | 81.(0)42.775.3011 Tel | info@everpure.co.jp Southeast Asia | 390 Havelock Road, | #04-01 King's Centre | Singapore 169662 | 65.6768.5800 Tel | cseverpure@pentair.com