

EVERPURE® DUAL HIGH FLOW COLDRINK® XC²

DELIVERS PREMIUM QUALITY WATER FOR HIGH VOLUME, MULTIPLE FOUNTAIN APPLICATIONS

Dual High Flow Coldrink XC²: EV9337-22 XC² Replacement Cartridge: EV9613-10 EC210 Prefilter Cartridge: EV9534-26



APPLICATIONS

Fountain

Multiple Simultaneous Applications

Serves Up To Eight (8) Machines At A Time Including Ice Machines, Coffee, Etc

FEATURES • BENEFITS

High volume central system delivers premium quality water to meet demanding peak periods

Sanitary cartridge replacement is simple, quick and clean; internal filter parts are never exposed to handling or contamination

Protects drink system seals, pump, tubing and small orifices from clogging, corrosion and abrasive wear

Proprietary Fibredyne™ II media inhibits the growth of bacteria on the filter media that can decrease product life Exclusive precoat filtration provides superior chlorine taste & odor reduction and micro-filters dirt and particles as small as 0.5 micron in size by mechanical means

Reduces chlorine taste & odor and other offensive contaminants that can adversely affect the taste of beverages


Improves the taste of fountain beverages and helps retain the drink's carbonation

NSF/ANSI Standard 53 certified to reduce cysts such as *Cryptosporidium* and *Giardia* by mechanical means

INSTALLATION TIPS	OPERATION TIPS	SIZING
Choose a mounting location suitable to support the full weight of the system when operating.	Change cartridges on a regular six (6) month preventative maintenance program.	Rated Capacity: 96,000 gallons (363,399 L)
		Service Flow Rate: Maximum 13.36 gpm (50.57 Lpm)
	Change cartridges when capacity is (50.57 Lpm) reached or when pressure falls below 10 psi (0.7 bar). Service flow rate must not exceed 13.36 gpm (50.57 Lpm). Always flush the filter cartridge at time of installation and cartridge change.	
Never use saddle valve for connection.		
Use 3/4" water line.		
Install vertically with cartridges hanging down.		
Allow 2 ½" (6.35 cm) clearance below the cartridge for easy cartridge replacement.		
Flush cartridges by running water through		

system for five (5) minutes at full flow.

EVERPURE® DUAL HIGH FLOW COLDRINK® XC² EV9337-22



EPA Est. No. 002623-IL-002

The contaminants or other substances removed or reduced by this drinking water system are not necessarily in your water. Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system. Systems certified for cyst reduction may be used with disinfected water that may contain filterable cysts.

SPECIFICATIONS

Service Flow Rate Maximum 13.36 gpm (50.57 Lpm)

Rated Capacity 96,000 gallons (363,399 L)

Pressure Requirements 10 - 125 psi (0.7 - 8.6 bar), non-shock

Temperature Limits 35 - 100°F (2 - 38°C)

Overall Dimensions 36" H x 37.5" W x 13.5" D (91.4 cm x 95.2 cm x 34.2 cm)

Inlet Connection 3/4" MNPT

Outlet Connection 3/4" MNPT

Shipping Weight 82 lbs (37.1 kgs)

Operating Weight 85 lbs (38.5 kgs)

Electrical Connection None required



System Tested and Certified by NSF International against NSF/ ANSI Standards 42 and 53 for the reduction of:

STANDARD NO. 42 – AESTHETIC EFFECTS

Chemical Reduction Taste & Odor Chlorine Mechanical Filtration

Nominal Particulate Class I

STANDARD NO. 53 – HEALTH EFFECTS Mechanical Filtration Cyst Turbidity

WARRANTY

Everpure water treatment systems by Pentair® (excluding replaceable elements) are covered by a limited waranty against defects in material and workmanship for a period of five years after date of purchase. Everpure replaceable elements (fitter cartridges and water treatment cartridges) are covered by a limited warranty against defects in material and workmanship for a period of one year after date of purchase. See printed waranty for details. Pentair will provide a copy of the warranty upon request.



WATER QUALITY SYSTEMS

EVERPURE-SHURFLO WORLD HEADQUARTERS, 1040 MUIRFIELD DRIVE, HANOVER PARK, IL 60133 USA • FOODSERVICE.PENTAIR.COM 800.942.1153 (US ONLY) • 630.307.3000 MAIN • 630.307.3030 FAX • CSEVERPURE@PENTAIR.COM EMAIL EVERPURE-SHURFLO AUSTRALIA, 1-21 MONASH DRIVE, DANDENONG SOUTH, VIC 3175 AUSTRALIA 011.1300 576 190 TEL • 011.61.39.562.7237 FAX • AU.EVERPURE@PENTAIR.COM EMAIL EVERPURE-SHURFLO CHINA, 21F CLOUD 9 PLAZA, NO 1118, SHANGHAI, 200052, CHINA 86.21.3211.4588 TEL • 86.21.3211.4580 FAX • CHINA.WATER@PENTAIR.COM EMAIL EVERPURE-SHURFLO INDIA, GREEN BOULEVARD, B-9/A, 7TH FLOOR - TOWER B SECTOR 62, NOIDA - 201301 91.120.419.9444 TEL • 91.120.419.9400 FAX • INDIACUSTOMER@PENTAIR.COM EMAIL EVERPURE-SHURFLO EUROPE, PENTAIR WATER BELGIUM BVBA, INDUSTRIEPARK WOLFSTEE, TOEKOMSTLAAN 30, B-2200 HERENTALS, BELGIUM +32.(0).14.283.504 TEL • +32.(0).14.283.505 FAX • SALES@EVERPURE-EUROPE.COM EMAIL EVERPURE-SHURFLO JAPAN INC., HASHIMOTO MN BLDG. 7F, 3-25-1 HASHIMOTO, MIDORI-KU, SAGAMIHARA-SHI KANAGAWA 252-0143, JAPAN 81.(0)42.775.3011 TEL • 81.(0)42.775.3015 FAX • INFO@EVERPURE.CO.JP EMAIL EVERPURE-SHURFLO SOUTHEAST ASIA, 390 HAVELOCK ROAD, #04-01 KING'S CENTRE, SINGAPORE 169662 65.6768.5800 TEL • 65.6737.5149 FAX • CSEVERPURE@PENTAIR.COM EMAIL All Pentair trademarks and logos are owned by Pentair, Inc. or its affiliates. All other registered and unregistered trademarks and logos are the property of their respective owners. Because we are continuously improving our products and services, Pentair reserves the right to change specifications without prior notice.

Pentair is an equal opportunity employer.