PENTAIR
EVERPURE

AC² FILTER CARTRIDGE

System Part Number:
EV9605-80 (1-pack)
EV9605-86 (6-pack)



FEATURES • BENEFITS

- Proprietary Micro-Pure® II media inhibits the growth of bacteria on the filter media that can decrease product life
- Exclusive precoat filtration provides chlorine taste & odor reduction and micro-filters dirt and particles as small as 0.2* micron
- Easy, quick-change cartridge replacement
- NSF/ANSI Standard 53 certified to reduce cysts such as Cryptosporidium and Giardia by mechanical means
- NSF/ANSI Standard 42 certified for Bacteriostatic Effects and the reduction of Chlorine Taste & Odor, and Particulate Class I
- NSF/ANSI Standard 401 certified for Microplastics Reduction

APPLICATIONS

- Cold cup vending
- Office coffee service

* Validated by ISO 17025 accredited lab for 99.999% reduction of Pseudomonas diminuta following the ASTM F838-05 protocol for the validation of 0.2 µm sterilizing grade filters.


EPA No. 002623-IL-002

INSTALLATION TIPS

- Install vertically and allow 2 1/2" (6.35 cm) clearance below the cartridge for easy removal and replacement.
- Flush cartridge by running water through the filter for five (5) minutes.
- Change cartridges when capacity is reached or when pressure falls below 10 psi (0.7 bar).
- It is recommended to replace cartridge at least once a year.

AC² FILTER CARTRIDGE

EV9605-80



Specifications

Overall Dimensions
10" L x 4" D (25.4 cm x 10.1 cm)

Service Flow Rate
Maximum 0.5 gpm (1.9 Lpm)

Rated Capacity
1,500 gallons (5,678 L)

Operating Pressure
10 - 125 psi (0.7 - 8.6 bar), non-shock

Water Temperature
35 - 100°F (2 - 38°C)

Electrical Connection
None required

For Pentair Everpure Product Warranties visit:
http://pentair.com/assets/foodservice-warranty

The contaminants or other substances removed or reduced by this drinking water system are not necessarily in your water. Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system.

Since the conditions under which our products may be used are beyond our control, we cannot accept any liability with respect to the improper installation, application and/or use of our products.

System Tested and Certified by NSF International against NSF/ ANSI Standards 42, 53, and 401 for the reduction of:

STANDARD NO. 42 – AESTHETIC EFFECTS
- Bacteriostatic Effects
- Chemical Reduction
  - Taste & Odor
  - Chlorine
- Mechanical Filtration
  - Nominal Particulate Class I

STANDARD NO. 53 – HEALTH EFFECTS
- Mechanical Filtration
  - Cyst
  - Turbidity

STANDARD NO. 401 – EMERGING COMPOUNDS / INCIDENTAL CONTAMINANTS
- Mechanical Filtration
  - Microplastics

PENTAIR

1040 Muirfield Drive | Hanover Park, IL 60133 | 800.942.1153 (US Only) 630.307.3000 Main | cseverpure@pentair.com | foodservice.pentair.com

All indicated Pentair trademarks and logos are property of Pentair. Third party registered and unregistered trademarks and logos are the property of their respective owners.

©2023 Pentair. All rights reserved.