

EF-3000 FULL FLOW DRINKING WATER SYSTEM



FEATURES • BENEFITS

- Commercial-grade water filtration for the home
- NSF/ANSI Standard 401 certified for the reduction of the incidental contaminants/emerging compounds listed in the performance data sheet
- ◆ NSF/ANSI Standard 53 certified to reduce cysts such as Cryptosporidium and Giardia by mechanical means
- Reduces particles as small as 0.5 micron in size by mechanical means
- ◆ The Pentair® Everpure® signature metal canister delivers commercial-grade durability
- Retains vital minerals found naturally in water to ensure the delicious taste of your water
- ◆ Built-in water shut-off allows for easier cartridge changes
- No separate faucet required

INSTALLATION TIPS

- Install vertically with cartridge hanging down.
- Flush new cartridge at full flow for three minutes to purge air.
- Space required: 5W x 20H x 5D in (13W x 50.8H x 13D cm) including 2½ inches of clear space under unit for cartridge change.

OPERATION TIPS


- Replace cartridge when capacity is reached, or when flow becomes too slow, but at least annually.
- Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system. Systems certified for cyst reduction may be used on disinfected water that may contain filterable cysts.

INCLUDES

Installation and operation manual

EPA Est. 002623-IL-002

EVERPURE EF-3000 FULL FLOW DRINKING WATER SYSTEM



SPECIFICATIONS

- System (Model / Part No.) EF-3000 / EV985700
- Flow Rate controlled at 2.2 gpm (8.3 Lpm)
- Inlet Size 3/8" 0C
- System Dimensions
 3.5" W x 16.81" H x 4.25" D
 (8.9W x 29.21H x 10.8D cm)
- System Weight 3.8 lbs (1.72 kg)
- Contaminant Reduction
 Chlorine Taste & Odor, Lead,
 Microplastics, Cysts: NSF/ANSI
 Standard 53 certified to reduce cysts
 such as Cryptosporidium and Giardia by
 mechanical means.

- Approximate Filter Life*
 Up to 1 Year
- Capacity 3,000 Gallons (11,356 Liters)
- Certifications
 NSF/ANSI Standard 42, 53, 401
- Pressure
 10-125 psi (0.7-8.6 bar) non-shock
- Temperature 35-100° F (2-38° C) cold water use only
- Replacement Cartridges
 (Model / Part No.)
 EF-3000 / EV985750 (1-pack)
 EF-3000 / EV985756 (6-pack)
- * Filter life dependent on gallon usage and overall incoming water quality.





The model EF-3000 is Tested and Certified by NSF International against NSF/ANSI Standards 42, 53, and 401 for the reduction of the claims specified on the Performance Data Sheet.

EPA Est. 002623-IL-002





Pentair Residential Filtration, LLC
13845 Bishops Dr. | Suite 200 | Brookfield, WI 53005 | United States
P: 262.238.4400 | Customer Service: 800.279.9404 | tech-support@pentair.com | pentair.com