

EASYCLEAN™

Aboveground D.E. Filter System

D.E. clarity with cartridge convenience.

We've paired our dependable OptiFlo® Aboveground Pump with our auto-regenerative EasyClean filter to create this high performance system for aboveground pools. Rugged, efficient and simple to operate, these perfectly matched components will keep your aboveground pool clean, clear and inviting—with minimal care.

EasyClean filter systems come in a variety of sizes to suit any aboveground pool configuration. And, the high performance OptiFlo pump is quiet and energy efficient, and will provide years and years of superior operation.

So if you're looking for top-end aboveground D.E. system performance with minimal maintenance, look no further than the EasyClean filter system from Pentair.

pentair.com/easyclean



▲
EASYCLEAN ABOVEGROUND
D.E. FILTER SYSTEM



EASYSOAN™ ABOVEGROUND D.E. FILTER SYSTEM

How the EasyClean D.E. filter works.

The EasyClean filter's coated D.E. cartridge traps dirt and debris. As the build-up on the cartridge element grows heavier, D.E. media and trapped particles can fall from the filter cartridge and settle at the bottom of the housing when the pump shuts off. Once the pump switches back on, much of the fallen D.E. media rises again and embeds itself back onto the filter cartridge while the debris stays behind. This automatic regeneration delivers maximum cleaning performance without the need to manually clean the cartridge nearly as often.

KEY FEATURES

- D.E. element**
 Ensures even water flow and uniform distribution of D.E. for optimum filtration efficiency.
- Automatically regenerates D.E. media during off cycle**
- Removable cartridge-style D.E. element**
 For quick, convenient cleaning.
- Cartridge-style D.E. element provides more square feet of filter area**
 Resulting in larger periods between cleaning.
- All models are equipped with unionized pump-to-filter connections**
 For fast and economical plumbing.
- Robust single-piece system base**
 designed for strength, durability and quiet operation.
- Lock ring with spring-loaded latches**
 For easier access and closure.
- 1-inch "no tool" filter drain**
 For quicker, easier maintenance and winterizing.



EASYSOAN ABOVEGROUND D.E. FILTER SYSTEM

PUMP KEY FEATURES

- Proprietary Totally Enclosed Fan-Cooled (TEFC) Motor**
 Enhanced design and balanced flow enable energy efficiency and reduce operating costs.
- Fiberglass-reinforced components**
 For superior strength, reliability and longevity.
- Large strainer basket with see-thru lid**
 For easy inspection and cleaning.

Model Number	Filter Area Sq. Ft.	D.E. Required (lbs.)	Turnover Capacity (Gallons)		
			8 hrs.	10 hrs.	12 hrs.
EC60	15	1.5	28,800	36,000	43,200
EC90	30	3.0	43,200	54,000	64,800

Flow rate and turnover capacity based on filter.



400 Regency Forest Dr | Cary, NC 27518 | United States | 800.831.7133 | pentair.com

All indicated Pentair trademarks and logos are property of Pentair. Third-party registered and unregistered trademarks and logos are the property of their respective owners. EasyClean™ and OptiFlo® are trademarks and/or registered trademarks of Pentair.

©2021 Pentair. All Rights Reserved.

P5-788 09/2021