

TAGELUS®

SAND FILTER WITH CLEARPRO TECHNOLOGY®

Now with superior filtration technology that dramatically improves water clarity.





TAGELUS® SAND FILTER WITH CLEARPRO TECHNOLOGY®

Maximum water clarity with minimal attention.

Tagelus filters have been installed in hundreds of thousands of pools for two primary reasons. First, is their consistency of performance over time. Second, because they go about their work without making work for you. With ClearPro Technology, performance is dramatically enhanced, but these same valued virtues remain intact.



Special "diffuser"

Creates a uniform sand bed that traps more dirt without impeding water flow or letting it race through too fast, resulting in more effective filtration and less frequent backwashings.

Combination sand-and-water drain

Speeds servicing and winterizing.

Six position Hi-Flow™ valve

Provides easy control of all filter functions and has a manual air relief valve and a sight glass to make inspection, maintenance and operation fast and easy.

One-piece fiberglass-reinforced tank

UV-resistant surface finish for years of unequaled strength and durability.

Dependability

Tagelus filters provide years of service with only periodic backwashing to remove trapped debris from the sand.


Threaded internal parts

For fast and easy service.


Model Number	Filter Area Sq. Ft.	Vertical Clearance*	Filter Diameter	Required Sand†(lbs.)	Flow Rate GPM**	Turnover Capacity (Gallons)		
						8 hrs.	10 hrs.	12 hrs.
TA 60D CP	3.1	57"	24.5"	325	60	28,000	36,000	43,200

[†]Use standard #20 silica sand.

The graphics at right illustrate, in a technically accurate way, the difference when ClearPro Technology is at work—far superior water clarity. The difference is particularly dramatic at night when pool lights can highlight particles in the water—not so when ClearPro Technology is on the job.



Traditional Sand Filter



Tagelus Filter With ClearPro Technology



1620 Hawkins Ave | Sanford, NC 27330 | United States | 800.831.7133 | pentair.com

All Pentair trademarks and logos are owned by Pentair plc. Tagelus®, ClearPro Technology® and HiFlow™ are trademarks and/or registered trademarks of Pentair Water Pool and Spa, Inc. and/or its affiliated companies in the United States and/or other countries. Because we are continuously improving our products and services, Pentair reserves the right to change specifications without prior notice.

^{*}Required clearance to remove the valve.

^{**}Maximum flow rate.

Maximum operating pressure is 50 psi.