



# PRESSURE TANKS

## MODEL VT19 MODEL VT20 MODEL VT36

- Tough, appliance-like finish for extended life
- Heavy gauge steel construction for maximum durability
- Replaceable air/water separator for easy maintenance
- Factory pre-charged at 40 PSI
- Convenient air valve location for quick hook up
- Universal jet pump mounting bracket included with VT19, VT20 and VT36
- Certified to ANSI/NSF 61



### PERFORMANCE

Model	Style	Warranty	Rated Size in Gallons	Actual Capacity in Gallons	Plumbing Connection	Tank Height
VT19	Vertical	5-year	42	19	1"	21"
VT20	Vertical	5-year	42	19	1"	33"
VT36	Vertical	5-year	82	35	1"	33"

Pressure Switch Setting	Type of Tank	Usable Water* per "Rated" Tank Size in Gallons	
		42	82
20-40	Standard	6.5	12.7
	Precharged	6.9	12.7
30-50	Standard	4.3	8.4
	Precharged	5.8	10.7
40-60	Standard	3.0	5.9
	Precharged	5.0	9.3

\*Usable water between pump cycles. The larger the usable water the less frequently the pump will cycle (turn off and on) thereby increasing pump life. Purchase the largest tank size possible for your application to maximize the life expectancy of your total water system.

### ORDERING INFORMATION

Model	UPC	Carton (L x W x H)	Cube	Pallet Qty.	Weight
VT19	0 22315 36357 1	20.81" x 20.81" x 22.31"	5.59	8	44 lbs.
VT20	0 17561 70007 2	16.75" x 16.75" x 29.31"	4.75	4	37.9 lbs.
VT36	0 17561 70008 9	20.81" x 20.81" x 34.31"	8.60	4	60.6 lbs.