

# FLOPLUS WFP-BB SERIES

Heavy Duty, High Flow Filtration Systems

## APPLICATIONS

- Ideal for low water pressure situations
- Whole house cyst, chlorine, and bad taste & odor reduction
- Well and city water installations
- Applications requiring safe, clean water



## FEATURES/BENEFITS

- Complete system, ready to install
- True depth filtration for high dirty-holding capacity
- Radial flow filtration for longer filter life and reduced maintenance
- Low pressure drop and high flow
- Drain simplifies cartridge change-outs
- 0.5 micron particulate reduction, while maintaining flows comparable to 10 micron carbon blocks



The WFP1-10BB and WFP1.5-20BB are Tested and Certified by Water Quality Association against NSF/ANSI Standard 53 for the reduction of the claims specified on the performance data sheet.

## MATERIALS OF CONSTRUCTION

- Cap: Polypropylene
- Sump: Reinforced Polypropylene
- O-ring: Buna-n



REDUCES



NSF/ANSI Standard 53  
Certified to reduce cysts  
such as *Cryptosporidium* and  
*Giardia* by mechanical means.



Chlorine Taste & Odor\*



Sediment\*

EPA Est. 086074-NH-001

\*Not Tested by WQA

## SYSTEM SPECIFICATIONS

MODEL	PART NUMBER	DIMENSIONS	MICRON RATING (NOMINAL) $\mu$	FLOW RATE	INITIAL $\Delta$ P (PSI) @ FLOW RATE (GPM)*	CHLORINE TASTE & ODOR REDUCTION @ FLOW RATE (GPM)*	INLET/OUTLET	CARTRIDGE SIZE
WFP1-10BB	152088	13 1/8" x 7 1/4" (333 mm x 184 mm)	0.5	10 gpm (37.8 Lpm)	4 psi @ 2 gpm (0.28 bar @ 7.6 Lpm)	>25,000 gal @ 2 gpm (94,635 L @ 7.6 Lpm)	1" NPT	4 5/8" x 9 3/4"
WFP1.5-20BB	152087	23 7/8" x 7 1/4" (606 mm x 184 mm)	0.5	25 gpm (94.6 Lpm)	4 psi @ 4 gpm (0.28 bar @ 15.2 Lpm)	>50,000 gal @ 4 gpm (189,270 L @ 15.2 Lpm)	1.5" NPT	4 5/8" x 20"

\*Based on manufacturer's internal testing.

Operating Pressure: 30-100psi [2.1-6.9 bar]

Temperature Range: 40-100°F [4.4-37.7°C]

Replacement cartridge kit for:

WFP1-10BB - 10" cartridge (555018-51)

WFP1.5-20BB - 20" cartridge (555017-51)

## SYSTEM INCLUDES

WFP1-10BB	
10" Grey Housing	153233
Black cap	154166
O-ring (W10-OR)	152032
10" Cartridge	555018-51
Mounting Bracket	150061
Wrench (SW-3)	150296
Drain Kit	244736

WFP1.5-20BB	
20" Grey Housing	153234
Black cap	145167
O-ring (W10-OR)	152032
20" Cartridge	555017-51
Mounting Bracket	150061
Wrench (SW-4)	144368
Drain Kit	244736



13845 BISHOPS DR., SUITE 200, BROOKFIELD, WI 53005 U.S.A.

P: 262.238.4400 | AMERICANPLUMBER.COM | CUSTOMER CARE: 800.279.9404 | tech-support@pentair.com

© 2017 Pentair Residential Filtration, LLC. All rights reserved.

§For a detailed list of where Pentair trademarks are registered, please visit [waterpurification.pentair.com/brands](http://waterpurification.pentair.com/brands).

Pentair trademarks and logos are owned by Pentair plc or its affiliates. Third party registered and unregistered trademarks and logos are the property of their respective owners.

300061 Rev B AU17