

# drinking water cartridges



## carbon impregnated cellulose

- ★ Economically priced
- ★ Dual purpose cartridge provides bad taste, odor, and chlorine taste & odor reduction, as well as sediment filtration\*
- ★ Design maximizes dirt holding capacity
- ★ For municipal/chlorinated water (not recommended for well water applications)
- ★ Recommended for point of use filtration



The W5CIP is Tested and Certified by NSF International.



## granular activated carbon (GAC)

- ★ Effective taste, odor, and chlorine taste & odor reduction
- ★ Cartridge design ensures that water passes through the entire length of the carbon bed, maximizing contact time.
- ★ Reduces particles as small as 20-micron in size by mechanical means



## carbon block cartridges

- ★ Excellent for bad taste, odor, and chlorine taste & odor reduction\*
- ★ Specialty blocks are capable of reducing lead and certain volatile organic compounds (VOCs)\*
- ★ NSF/ANSI Standard 53 certified to reduce cysts such as Cryptosporidium and Giardia by mechanical means.



The W.5CB and WLC-R are Tested and Certified by NSF International.

\* As tested by American Plumber  
Certain states require system  
registration or certification for  
health-related reduction claims

			housings																
			3/8" SlimLine® Housings	W385-PR (5")	W38-PRA (10")	W38-PRB (10")	W38-PRQC (10")	3/4" Standard Housings	W34-PR (10")	WC34-PRB (10")	WC34-PR (10")	WVC34 (10")	W34-PRB (10")	3/4" High Temp Housing	WH34 (10")	3/4" Stainless Steel	ST-1 (10")	ST-2 (20")	ST-3 (30")
cartridges	Drinking Water	Micron Rating †																	
	Filter Cartridge		Flow Rate * (gpm)																
	W.5CB478	0.5		1															
	W5CIP478	5		1															
	WGC478	—		1															
	W.5CB	0.5			1	1	1												
	WLC-R	0.5			0.6	0.6	0.6												
	W5CIP	5			5	5	5		5	5	5	5	5		5		5	10	15
WCC	—			1	1	1													

† Micron ratings are nominal

\* Flow rates are calculated for cartridges according to the housing in which they are being used

Model	Part	Medium	Micron Rating (nominal)	Max. Flow Rate (gpm)	Diameter	Length
Carbon Impregnated Cellulose - reduces particles as small as 5 micron in size by mechanical means						

W5CIP478	155022-52	Carbon Impregnated Cellulose	5	2	2-1/2"	4-7/8"
W5CIP	155002-52	Carbon Impregnated Cellulose	5	5	2-5/8"	9-3/4"

Model	Part	Medium	Chlorine Taste & Odor Reduction @ Flow Rate**	Max. Flow Rate (gpm)	Diameter	Length
Granular Activated Carbon (GAC)						

WGC478	155110-51	Granular Activated Carbon	>750 Gal. @ 0.5 GPM	1	2-7/8"	4-7/8"
WCC	155155-51	Granular Activated Coconut Carbon	>500 Gal. @ 1 GPM	1	2-7/8"	9-3/4"

Model	Part	Medium	Reduces**	Micron Rating (nominal)	Chlorine Taste & Odor Reduction @ Flow Rate**	Lead (gallons)	VOCs (gallons)	Max. Flow Rate	Diameter	Length
Carbon Block - reduces particles as small as 5 micron in size by mechanical means										

W5CB478	155169-51	Acid-washed Bituminous	Chlorine Taste & Odor, Cyst	0.5	>3,000 Gal. @ 1 GPM	N/A	N/A	1	2-7/8"	4-7/8"
W5CB	155162-51	Acid-washed Bituminous	Chlorine Taste & Odor, Cyst	0.5	>20,000 Gal. @ 1 GPM	N/A	N/A	1	2-7/8"	9-3/4"
WLC-R	155268-51	Acid-washed Bituminous	Chlorine Taste & Odor, Cyst, Lead & VOC	0.5	>20,000 Gal. @ 0.6 GPM	600**	300**	0.6	2-7/8"	9-3/4"

\*\* As tested by American Plumber Certain states require system registration or certification for health-related reduction claims