

Stainless Steel Shallow Well Jet Pumps

With Built-in Pressure Switch

Heavy-Duty Stainless Steel Construction

For the highest corrosion-resistance

Superior Performance

At depths to water of 25' or less

Heavy-Duty Dual-Voltage Motor

Preset at 230V

Self-Priming After Pump Housing Is Initially Filled

Check valve or foot valve required, sold separately



1 HP 17.5 GPM
FP4832

3/4 HP 11 GPM
FP4822

PERFORMANCE (GPM)							MAX PRESSURE SHUTOFF	VOLTAGE	PRESSURE SWITCH	
DEPTH TO WATER	0'	5'	10'	15'	20'	25'			ON	OFF
FP4832	17.5	16.2	14.6	12.6	10.6	7.5	81 PSI	115/230	30	50
FP4822	11.0	11.0	11.0	11.0	9.0	7.2	64 PSI	115/230	30	50

• All performance shown in gallons per minute at 40 PSI discharge pressure

MODEL	WARRANTY	UPC	CARTON DIMENSIONS	PALLET QTY.	WEIGHT
FP4832	1 YEAR	022315160613	21.313" x 11.313" x 12.625"	18	33.75 LBS.
FP4822	1 YEAR	022315160606	21.313" x 11.313" x 12.625"	18	29.05 LBS.

Includes:

Factory-installed 30/50 preset pressure switch, detailed owner's manual

