# **Thermoplastic**

Convertible Jet Pumps

For Deep or Shallow Wells

## **Superior Performance**

At depths to water of 110' or less

### Fiberglass-Reinforced Thermoplastic Pump Housing

For the highest corrosion resistance

#### **Heavy-Duty Dual-Voltage Motor**

3/4 HP & 1 HP preset at 230V 1/2 HP preset at 115V;

# **Self-Priming After Pump Housing Is Initially Filled**

Foot valve included with Jet Kit, sold separately

#### **Prewired Pressure Switch**

Preset for 30/50 PSI operation

# **Built-in Pressure Regulator**

Includes:

Factory-installed 30 PSI gauge, preset pressure switch, detailed owner's manual

1 HP 9 GPM FP4332

3/4 HP 7.5 GPM FP4322

1/2 HP 5.9 GPN FP4312

PERFORMANCE																						
MODEL/ UPC	НР	GPM	VOLTS		GALLONS PER MINUTE PUMPED AT DIFFERENT DEPTHS TO WATER IN FEET												PRESS. SHUTOFF	JET KIT	PRESS. SWITCH		CARTON DIMS.	WT.
				5'	10'	15'	20'	30'	40'	50'	60'	70'	80'	90'	100'	110'	AT MAX DEPTH	JET KIT	ON	OFF	#1. C. LEON	(LBS.)
FP4332 022315100688	1	9	230/115				9.0	8.4	7.3	6.2	5.0	4.4	2.9	2.0	-	-	56 PSI	FP4800			20.94 x 12.31	
Deep Well with 4" dia. casing or larger																			30	50	x 12.19 24/PALLET	30.35
Deep Well with 2" dia. casing							8.4	7.8	6.7	5.6	4.4	3.5	3.0	2.5	2.0	1.4	62 PSI	FP4840				
Shallow Well of 25' or less				20.7	18.3	15.8	12.3	8.5	-	-	-	-	-	-	-	-	-	FP4875				
FP4322 022315100671	3/4	7.5	230/115				7.5	6.5	5.1	4.0	3.0	2.5	1.8	1.5	1.0		56 PSI	FP4800			20.94 x 12.31	
Deep Well with 4" dia. casing or larger																			30	50	x 12.31 x 12.19	27.7
Deep Well with 2" dia. casing							6.8	6.2	4.8	3.7	2.6	2.1	1.5	1.2	0.8	-	53 PSI	FP4840			24/PALLET	
Shallow Well of 25' or less				15.3	13.8	11.8	9.2	6.8	-	-	-	-	-	-	-	-	-	FP4875	1		Z4/1 ALLE1	
FP4312 022315100664	1/2	5.9	230/115				5.9	4.5	3.5	2.8	2.3	1.7	-			-	54 PSI	FP4800			20.94 x 12.31	
Deep Well with 4" dia. casing or larger																			30	50	x 12.31 x 12.19	54
Deep Well with 2" dia. casing							5.3	4.3	3.4	2.5	1.9	1.5	-		-	-	-	FP4840			24/PALLET	
Shallow Well of 25' or less			9.0	7.8	6.6	5.7	4.3										FP4875					

All performances shown in gallons per minute at 40 PSI discharge pressure.