

**Non-Submersible**

# Pedestal Sump Pumps

**Thermoplastic or Cast Iron/Stainless Steel****Rugged Construction**

Designed for a high level of corrosion resistance

**Durable Motor**

Thermal overload protection

**1/3 HP** 3480 GPH  
FPPSS3000**1/3 HP** 3480 GPH  
FPPM3600D

| PERFORMANCE (GPH)                    |      |      |      |      |           | FLOAT SWITCH |     | SOLIDS HANDLING |
|--------------------------------------|------|------|------|------|-----------|--------------|-----|-----------------|
| DISCHARGE HEIGHT ABOVE PUMPING LEVEL | 0'   | 5'   | 10'  | 15'  | MAX. LIFT | ON           | OFF |                 |
| FPPSS3000                            | 3480 | 3200 | 2700 | 2000 | 20'       | 14"          | 6"  | 1/4"            |
| FPPM3600D                            | 3000 | 3000 | 2460 | 1620 | 20'       | 14"          | 6"  | 1/4"            |

| MODEL     | WARRANTY | UPC          | CARTON DIMENSIONS     | PALLET QTY. | WEIGHT    |
|-----------|----------|--------------|-----------------------|-------------|-----------|
| FPPSS3000 | 2 YEAR   | 022315101999 | 8.25" x 7.25" x 33.5" | 30          | 17.4 LBS. |
| FPPM3600D | 1 YEAR   | 022315100084 | 8.25" x 7.25" x 33.5" | 30          | 12.8 LBS. |

Includes:

Detailed owner's manual

Check valve replacement recommended

