



# Emergency Battery Backup

## Pre-Assembled Sump Pump System

### Link<sub>2</sub>O™ Remote Monitoring

Constantly monitors system conditions, and alerts you (by cellphone or computer) when your basement is in danger of flooding. At home, at work, or across the globe – you are protected and informed.

### Proprietary Smart Charging Technology

Recharges battery 25% faster and extends battery life.

### High Performance Pump

Removes up to 83% more gallons per charge than the leading competitor.

### 1/2 HP Primary Pump

Removes 4200 gallons per hour.



LEARN MORE AT:  
[www.mylink2o.com](http://www.mylink2o.com)

## 12V 4200 GPH FPCC5030

PERFORMANCE (GPH)							SOLIDS HANDLING
DISCHARGE HEIGHT ABOVE PUMPING LEVEL	0'	5'	10'	15'	20'	MAX. LIFT	
<b>PRIMARY PUMP</b>	4200	3660	3000	2160	960	22'	3/16"

DISCHARGE HEIGHT ABOVE PUMPING LEVEL	0'	5'	10'	14'	MAX. LIFT	SOLIDS HANDLING
<b>BACKUP PUMP</b>	2700	2040	1260	360	15'	3/16"

FEATURE	FLOTEC® FPCC3350	COMPETITION	FLOTEC ADVANTAGE
Max Flow (12.7V)	2700	2200	22% more flow
Flow @ 10' (12.7V)	1260	900	40% more flow
Max Head	15'	14'	7% higher head
Gallons per charge @ 10' head	11,500	6300	83% more gallons per charge
Charger	2.0 AMPS	1.6 AMPS	25% faster charging

\*Performance data based on internal testing using BAT75

MODEL	WARRANTY	UPC	CARTON DIMENSIONS	PALLET QTY.	WEIGHT
<b>FPCC5030</b>	2 YEAR	022315377592	18.25 x 10.13 x 16.63	20	22 LBS.



Operates in 14" basin or larger. Includes: Battery case control unit, 12V pump, Reed switch, AC Power supply, Wireless gateway, 1/2 HP primary pump - w/vertical switch, pre-plumbed w/wye connection & check valves

Compatible with flooded and sealed AGM deep cycle lead acid batteries.

For best performance use Flotec BAT40 or BAT75 sealed AGM batteries.

293 Wright Street, Delavan, WI 53115

For Questions or Installation Instructions: [www.flotecwater.com](http://www.flotecwater.com) 1-800-365-6832