PENTAIR

## **CONVERTIBLE JET PUMPS**

MODEL FP4205 1/2 HP MODEL FP4207 3/4 HP MODEL FP4210 1 HP

- Superior performance at depths of water 70' or less
- Rugged cast iron construction
- Ready-to-install, heavy-duty, dual-voltage motor 1/2 HP preset at 115V; 3/4 and 1 HP models preset at 230V
- Self-priming after pump housing is initially filled, check valve or foot valve required
- Pre-wired pressure switch preset for 30-50 PSI operation
- 1" discharge, 1-1/4" suction, 1" drive



## **PERFORMANCE - SHALLOW WELL OF 25 FEET OR LESS**

Model	HP	Voltage	Full Load Amps	Pressure Switch		GPM Pumped at Different Depths to Water <sup>^</sup>				Max Pressure	
				On	Off	0'	5'	10'	15`'	20'	Shut-off
FP4205	1/2	115/230	7.0/3.5	30	50	10	9.5	9.0	8.0	6.5	54 PSI
FP4207	3/4	115/230	11.0/5.5	30	50	16	14.5	13.5	12	10	70 PSI
FP4210	1	115/230	11.0/5.5	30	50	17	15	13.5	12.5	10	70 PSI

## PERFORMANCE - DEEP WELL WITH 4" DIAMETER CASING OR LARGER

Model		Max Pressure Shut-off				
nouei	30'	40'	50'	60'	70'	Plax Pressure Shut-on
FP4205	3.5	3.0	2.5	2.0	1.0	65 PSI
FP4207	7.0	6.0	4.5	3.5	2.5	65 PSI
FP4210	10.0	8.0	6.0	4.5	3.0	65 PSI

All performances shown in gallons per minute at 40 PSI (pound per square inch) discharge pressure at top of well.

## **ORDERING INFORMATION**

Model	UPC	Carton (L x W x H)	Cube (FT)	Pallet Qty.	Weight
FP4205	0 22315 36169 0	17.32" x 13.34" x 10.45"	1.397	48	21 lbs.
FP4207	0 22315 36303 8	17.32" x 13.34" x 10.45"	1.397	48	21 lbs.
FP4210	0 22315 36170 6	17.32" x 13.34" x 10.45"	1.397	48	24 lbs.

