



2-Wire, 4"

Submersible Well Pumps



**For Residential Water Systems
or Agricultural Applications**

Pumps to depth of 300'

High Performance

Proven floating stack impeller design for
sand resistance and reduced sand locking

Durable Construction


Stainless steel pump and motor housing



1/2 HP – 1 HP 10-14 GPM

PERFORMANCE																	
MODEL/ UPC	HP	GPM SERIES	VOLTS	GALLONS PER MINUTE PUMPED AT DIFFERENT DEPTHS TO WATER IN FEET											DISCHARGE	CARTON DIMS. (IN INCHES)	WEIGHT (LBS.)
				20'	40'	60'	80'	100'	150'	200'	250'	300'	350'	400'			
FP2211 022315155787	1/2	10	115	13.2	12.2	10.9	9.6	8.1	2	-	-	-	-	-	1-1/4"	4.8 x 4.8 x 34	21
FP2212 022315100800	1/2	10	230	13.2	12.2	10.9	9.6	8.1	2	-	-	-	-	-	1-1/4"	4.8 x 4.8 x 33	21
FP2222 022315100817	3/4	10	230	14.8	14.2	13.4	12.6	11.7	8.8	5.2	-	-	-	-	1-1/4"	4 x 4.8 x 34.3	24
FP2232 022315100824	1	10	230	-	-	14.7	14	13.4	11.7	9.7	7.3	4.4	-	-	1-1/4"	4.6 x 5 x 29	27

*All performances shown in gallons per minute at 40 PSI discharge pressure at the top of the well.

 **Optimal pump performance**