

Cast Iron Shallow Well Jet Pumps

With Built-in Pressure Switch

Rugged Cast Iron Construction

For heavy-duty applications

Reliable Performance

At depths to water of 25' or less

Ready-to-Install Motor

Operates at 115V

Self-Priming After Pump Housing Is Initially Filled

Check valve or foot valve required,
sold separately



3/4 HP
8.3 GPM
FP4107

1/2 HP
5.6 GPM
FP4105

PERFORMANCE (GPM)							MAX PRESSURE SHUTOFF	VOLTAGE	PRESSURE SWITCH	
DEPTH TO WATER	0'	5'	10'	15'	20'	25'			ON	OFF
FP4107	8.3	7.8	7.3	6.7	6.1	5.0	74 PSI	115	30	50
FP4105	5.6	5.1	4.5	4.1	3.5	3.1	63 PSI	115	30	50

All performances shown in gallons per minute at 40 PSI discharge pressure.

MODEL	WARRANTY	UPC	CARTON DIMENSIONS	PALLET QTY.	WEIGHT
FP4107	1 YEAR	022315322486	15.200" x 9.4" x 11"	27	23.55 LBS.
FP4105	1 YEAR	022315176225	15.200" x 9.4" x 11"	27	24.25 LBS.

Includes:

Factory-installed 30/50 preset pressure switch, detailed owner's manual

