

Cast Iron Centrifugal Pumps

Rugged Pump Housing

Durable, cast iron construction

Superior Performance

At depths to water of 25' or less

Heavy-Duty Dual-Voltage Motor

Preset at 230V

Easy Installation

Discharge can be rotated to horizontal or vertical installations

1-Year Warranty



1 HP 69 GPM
FP5532

3/4 HP 67 GPM
FP5522

1/2 HP 55 GPM
FP5512

PERFORMANCE

MODEL/UPC	HP	MAX. PRESS.	VOLTS	DISCHARGE PRESSURE (PSI)					NPT PIPE SIZE		CARTON DIMS. (IN INCHES)	WT. (LBS.)
				25	30	35	40	45	SUCTION	DISCH.		
FP5532 022315135949	1	49	230/115	47	40	35	29	17	1-1/4"	1"	19.813 x 10.063 x 10.818 40/PALLET	41.2
FP5522 022315135932	3/4	43	230/115	31	25	21	13	-	1-1/4"	1"	19.813 x 10.063 x 10.818 32/PALLET	32.15
FP5512 022315135925	1/2	36	230/115	22	13	2	-	-	1-1/4"	1"	19.813 x 10.063 x 10.818 32/PALLET	30.10

Includes:
Threaded ports for pressure gauge and drain plug, detailed owner's manual