

Thermoplastic Utility/ Waterfall Pump

Submersible

High-Output Performance

Pumps up to 3000 gallons per hour

Thermoplastic Construction

Designed for years of trouble-free operation

Oil-Free Motor

Safe for fish and plants

Ceramic Seal Design

Allows for continuous operation



4/10 HP 3000 GPH
FP0S3000X

| PERFORMANCE (GPH) | | | | | | | HP | OUTLET |
|--------------------------------------|------|------|------|------|-----|-----------|------|-------------------------------|
| DISCHARGE HEIGHT ABOVE PUMPING LEVEL | 0' | 5' | 10' | 15' | 20' | MAX. LIFT | | |
| FP0S3000X | 3000 | 2500 | 1900 | 1320 | 750 | 25' | 4/10 | 1-1/4" with multiple fittings |

| MODEL | WARRANTY | UPC | CARTON DIMENSIONS | PALLET QTY. | WEIGHT |
|-----------|----------|--------------|-----------------------|-------------|----------|
| FP0S3000X | 1 YEAR | 022315164819 | 6.44" x 11.8" x 6.44" | 90 | 9.6 LBS. |



Includes:

Three discharge fittings: 1/2", 3/4" and 1" barbed hose, 1" reducer, garden hose adapter