

Complete

Jet & Tank System

Ideal for Compact Installations

Where space is at a premium

Superior Performance

At depths to water of 25' or less

19-Gallon Pressure Tank, Precharged to 25 PSI

Corrosion-resistant, heavy-gauge steel construction with baked-on finish

Fiberglass-Reinforced Thermoplastic Pump Housing

For the highest corrosion and sand-abrasion resistance

Heavy-Duty Dual-Voltage Motor

Preset at 230V

Built-In Check Valve



3/4 HP 10 GPM FP2521

PERFORM	CE ((GPM	D	MAX PRESSURE		DISCHARGE	VOLTAGE	PRESSURE SWITCH		
DEPTH TO WATER	5'	10'	15'	20¹	SHUTOFF	SIZE	SIZE		ON	OFF
FP2521	10.2	8.7	7.6	5.8	70 PSI	1-1/4"	1"	115/230	30	50

All performances shown in gallons per minute at 40 PSI discharge pressure.

WARRANTY	UPC	CARTON DIMENSIONS	PALLET QTY.	WEIGHT	
1 YEAR	022315381544	44.25" x 17.25" x 33"	2	78 LBS.	

Includes: Factory-installed 30/50 preset pressure switch, detailed owner's manual

293 Wright Street, Delavan, WI 53115
For Questions or Installation Instructions:
www.flotecwater.com 1-800-365-6832

