

# Cast Iron Convertible Jet Pumps

For Deep or Shallow Wells

### Rugged Pump Housing

Durable cast iron construction

### Superior Performance

At depths to water of 100' or less  
(jet kit sold separately)

### Heavy-Duty Dual-Voltage Motor

3/4 HP preset at 230V  
1/2 HP preset at 115V;

### Prewired Pressure Switch

Preset for 30/50 PSI operation

### Self-Priming After Pump Housing Is Initially Filled

Foot valve included with Jet Kit, sold separately

### Built-in Pressure Regulator



**3/4 HP 7.5 GPM**  
FP4222

**1/2 HP 5.9 GPM**  
FP4212

PERFORMANCE																								
MODEL/ UPC	HP	GPM	VOLTS													PRESS. SHUTOFF AT MAX DEPTH	JET KIT	PRESS. SWITCH		CARTON DIMS. (INCHES)	WEIGHT (LBS.)			
				5'	10'	15'	20'	30'	40'	50'	60'	70'	80'	90'	100'			ON	OFF					
<b>FP4222</b> 022315100640	<b>3/4</b>	<b>7.5</b>	230/115				7.5	6.5	5.1	4.0	3.0	2.5	1.8	1.5	1.0	56 PSI	FP4800	30	50	17.32 x 13.34 x 10.45	24			
				<b>Deep Well</b> with 4" dia. casing or larger																		53 PSI	FP4840	
				<b>Deep Well</b> with 2" dia. casing							6.8	6.2	4.8	3.7	2.6	2.1	1.5	1.2	0.8	53 PSI	FP4840			48/PALLET
				<b>Shallow Well</b> with single pipe				11.9	10.8	9.5	7.5	-	-	-	-	-	-	-	-	63 PSI	FP4855			
<b>FP4212</b> 022315100633	<b>1/2</b>	<b>5.9</b>	230/115				5.9	4.5	3.5	2.8	2.3	1.7	-	-	-	54 PSI	FP4800	30	50	17.32 x 13.34 x 10.45	21			
				<b>Deep Well</b> with 4" dia. casing or larger																			54 PSI	FP4840
				<b>Deep Well</b> with 2" dia. casing							5.3	4.3	3.0	2.5	1.9	1.5	1.1	-	-	54 PSI	FP4840			48/PALLET
				<b>Shallow Well</b> with single pipe				7.9	7.1	6.3	5.4	-	-	-	-	-	-	-	-	60 PSI	FP4855			

All performances shown in gallons per minute at 40 PSI discharge pressure.

Includes: Factory-installed 30/50 preset pressure switch, detailed owner's manual