



**Zinc**

# Sump Pump

**High-Output Performance**

**Corrosion resistant zinc construction**

Dissipates heat quickly and extends motor life

**Uni-body motor housing**

Eliminates leak points and maximizes pump life

**Stainless steel fasteners and hardware**

Superior quality

**Quadra Seal™ technology**

Provides superior motor protection over single seal designs

**Smooth Flow Hydraulics™**

Deliver high performance for demanding applications

**Vertical Float Switch**

Operates in 10" basins or larger



**1 HP 6660 GPH**  
FPZT7550

**3/4 HP 6360 GPH**  
FPZT7450

**1/2 HP 6000 GPH**  
FPZT7350

PERFORMANCE (GPH)								FLOAT SWITCH		SOLIDS HANDLING
DISCHARGE HEIGHT ABOVE PUMPING LEVEL	0'	5'	10'	15'	20'	25'	MAX. LIFT	ON	OFF	
FPZT7350	6000	5,100	4,140	2,940	1,380	-	23'	7.5"	3"	3/8"
FPZT7450	6,360	5,460	4,500	3,420	2,100	420	26'	7.5"	3"	3/8"
FPZT7550	6,660	5,880	4,980	4,020	2,880	1,500	29'	7.5"	3"	3/8"

MODEL	WARRANTY	UPC	CARTON DIMENSIONS	PALLET QTY.	WEIGHT
FPZT7350	3 YEAR	022315368118	10" x 8" x 13.5"	72	15 LBS.
FPZT7450	3 YEAR	022315368002	10" x 8" x 13.5"	72	15 LBS
FPZT7550	3 YEAR	022315368309	10" x 8" x 13.5"	72	15 LBS

Includes: 1 1/2" NPT discharge, 8' grounded power cord, piggyback-style switch for automatic or manual operation, detailed owner's manual

Check Valve replacement is recommended

293 Wright Street, Delavan, WI 53115

For Questions or Installation Instructions:

[www.flotecwater.com](http://www.flotecwater.com) 1-800-365-6832

