

MODEL: S4S/SB4S — Standard Single Seal Sewage Ejector Pumps**Physical Data:**

| | |
|----------------|------------------------------|
| DISCHARGE SIZE | 4" |
| IMPELLER TYPE | BALANCED, SEMI OPEN, 2 VANE |
| CABLE LENGTH | 35' STANDARD 50' OPTIONAL |

Liquid Handling:

| | |
|---------------------|-------------|
| SOLIDS SIZE | 3" |
| MAXIMUM LIQUID | 140°F |
| ACCEPTABLE PH RANGE | 6 - 9 |
| SPECIFIC GRAVITY | 0.9 - 1.1 |
| VISCOSITY | 28 - 35 SSU |

Temperature:

| | |
|-----------------|--|
| MAXIMUM STATOR | 311°F |
| OIL FLASH POINT | 390°F |
| HEAT SENSOR | Open: 257°F MAX./239°F MIN. Closed: 194°F MAX./119°F MIN. |

Technical Data:

| | | |
|---------------------------|---|------------------------------|
| POWER CORD TYPE | SOOW, W | |
| MATERIALS OF CONSTRUCTION | MOTOR HOUSING | CAST IRON ASTM A-48 CLASS 30 |
| | CASING | CAST IRON ASTM A-48 CLASS 30 |
| | IMPELLER | DUCTILE IRON ASTM 536 |
| | MOTOR SHAFT | 400 STAINLESS STEEL |
| | HARDWARE | 300 SERIES STAINLESS STEEL |
| | "O" RINGS | NITRILE |
| MECHANICAL SEALS | Standard: CARBON/CERAMIC/NITRILE, TYPE 21 | |
| UPPER BEARING (RADIAL) | SINGLE ROW — BALL | |
| LOWER BEARING | (THRUST) SINGLE ROW — BALL | |