

S4B(X)P - HYDROMATIC PREMIUM EFFICIENT (HPE) SUBMERSIBLE SOLIDS HANDLING PUMPS

PHYSICAL DATA

DISCHARGE SIZE	4"
SOLIDS SIZE	3"
IMPELLER TYPE	BALANCED, ENCLOSED, 2 VANE
CABLE LENGTH	35' STANDARD, 50', 75', 100' OPTIONAL
PAINT	PAINTED AFTER ASSEMBLY. DARK GREEN, WATER REDUCIBLE ENAMEL, ONE COAT, AIR DRIED.

TEMPERATURE

MAXIMUM LIQUID	104° F LABELED/140° F UNLABELED
MAXIMUM STATOR	356° F (180° C)
OIL FLASH POINT	309° F
HEAT SENSOR OPEN	275° F MAX./257° F MIN.
HEAT SENSOR CLOSED	204° F MAX.

TECHNICAL DATA

MOTOR	PREMIUM EFFICIENT NEMA MG1, IEC 60034 -30 LEVEL IE3				
POWER CORD TYPE	W OR SOOW, WATER RESISTANT, 600V, 90° C				
SENDER CORD	SOOW, 18-5, WATER RESISTANT, 600V, 90° C, 5.5 AMPS				
MATERIALS OF CONSTRUCTION	MOTOR HOUSING	CAST IRON	ASTM	A-48	CLASS 30
	CASING	CAST IRON	ASTM	A-48	CLASS 30
	IMPELLER	DUCTILE IRON	ASTM	A-536	CLASS 65
	CASING WEAR RING	BRONZE	ASTM	B-584-836	ALLOY 115
	MOTOR SHAFT	416 STAINLESS STEEL			
	HARDWARE	300 SERIES STAINLESS STEEL			
	O-RINGS	NITRILE			
MECHANICAL STANDARD SEALS	UPPER - C/SIC TYPE 2100, LOWER - C/SIC TYPE 2				
UPPER BEARING	(RADIAL) SINGLE ROW - BALL				
LOWER BEARING	(THRUST) DOUBLE ROW, ANGULAR CONTACT - BALL				