
PENTAIR MYERS

STAINLESS STEEL UTILITY PUMP MODEL DU25

The Myers DU25 1/4 HP Stainless Steel Utility Pump is ideal for dewatering shallow flooded areas such as basements, window wells, rooftops, ponds, and stock tanks.



PERFORMANCE



ORDERING INFORMATION

MODEL NUMBER	HP	MAX Capacity	MAX HEAD	DISCHARGE NPT	SOLIDS Handling	VOLTS	FULL LOAD AMPS	PHASE	CORD LENGTH	SWITCH
DU25M1	1/4	19	23	1-1/4″	1/8″	115	2.5	1	15″	А

293 Wright St Delavan, WI 53115 Ph: 888.987.8677 Fx: 800.426.9446 490 Pinebush Rd,Unit 4 Cambridge, Ontario N1T 0A5, Canada Ph: 800.363.7867 Fx: 888.606.5484 pentair.com

All indicated Pentair trademarks and logos are property of Pentair. Third party registered and unregistered trademarks and logos are the property of their respective owners. Because we are continuously improving our products and services, Pentair reserves the right to change specifications without prior notice. Pentair is an equal opportunity employer.

©2023 Pentair. All Rights Reserved.

FEATURES

- Pumps up to 19 GPM.
- Extra durable for heavy-duty use.
- Includes 1″ x 3/4″ garden hose adapter.
- Pumps standing water down to 1/8".
- Rated for continuous duty.
- CSA listed.

SPECIFICATIONS

- Capacities: 19 GPM, 71.9 LPM
- **Shut-Off Head** : 23', 7 m
- **Operations**: Manual
- **Pump-Down Range**: 3/8" 9.5 mm
- Solids Handling: 1/8" 3.2 mm
- Liquids Handling: Clear Water
- Continuous Liquid Temp.: 77° F 22° C
- Motor: 1/4 HP, PSC
- Electrical: 115V, 60Hz, 2.5A, 3450 RPM
- Mechanical Seal: Dual lip seal with ceramic shaft sleeve
- Housing: Stainless steel
- Impeller: Polyphenylene oxide
- **Power Cord**: 15' Three-prong, SJTW 18-3
- Discharge NPT: 1-1/4"
- **Dimensions**: 9"H × 7"W