

QUICK-CHANGE FILTRATION SYSTEMS

DESIGNED FOR EASY INSTALLATION AND CARTRIDGE CHANGE



Pentair Quick-Change Filtration Systems are designed for easy installation and cartridge change. 1/4" or 3/8" push fittings, as well as 1/4" compression fittings, on the inlet and outlet sides of the filter head allow effortless installation.

The cartridge filter is easily changed with a quarter-turn of the filter. Water is automatically shut off during the change of the filter through the auto shut-off feature built into the filter head. This feature eliminates the need for additional shut-off valves to and from the filter system.

The Quick-Change Filter System offers several cartridge options to meet the demands of varying water conditions. The granular activated carbon cartridge offers chlorine taste and odor performance with low pressure drop. The EP carbon block filter offers superior chlorine taste and odor performance with 5 micron sediment reduction by mechanical means.

FEATURES/BENEFITS

Easy to install, easy filter change
 Reversible metal brackets for 1, 2 or 3 cartridges
 1/4-inch or 3/8-inch John Guest push-fit connections available

1/4-inch compression connections available for flex hose connections
 Cartridge models to choose from to meet specific application needs

APPLICATIONS

Under-sink drinking water
 Refrigerator/icemaker
 Pre/post RO membrane
 Vending machine

Ice machine
 Coffee machine
 Other OEM applications



QC10-EP and QC10-GAC are Tested and Certified by NSF International to NSF/ANSI 42 for the reduction of the claims specified on the Performance Data Sheet



QC10-CBR Tested and Certified by NSF International to NSF/ANSI 42 and 53 for the reduction of the claims specified on the Performance Data Sheet

SPECIFICATIONS AND PERFORMANCE

PART #	MODEL #	CARTRIDGE COLOR	FILTER LIFE	FLOW RATE	RATING (NOMINAL)	1/4" THREADED	1/4" JG PUSH FIT	3/8" JG PUSH FIT
158682	QC10-CBR	White	500 gallons (1890 L)	0.5 gpm (1.9 Lpm)	0.5-micron	•	•	•
158683	QC10-EP	White	1,500 gallons (5670 L)	0.5 gpm (1.9 Lpm)	5-micron	•	•	•
158684	QC10-GAC	Blue	2,500 gallons (9460 L)	0.75 gpm (2.8 Lpm)	-	•	•	•
158723	QC10-TSGAC*	Blue	1,700 gallons (6435 L)	0.75 gpm (2.8 Lpm)	-	-	•	•

*Not Performance Tested or Certified by NSF.



13845 BISHOPS DR., SUITE 200, BROOKFIELD, WI 53005 USA
P: 262.238.4400 | WATERPURIFICATION.PENTAIR.COM | CUSTOMER CARE: 800.279.9404 | tech-support@pentair.com

© 2018 Pentair Residential Filtration, LLC. All rights reserved.

§For a detailed list of where Pentair trademarks are registered, please visit waterpurification.pentair.com/brands. Pentair trademarks and logos are owned by Pentair plc or its affiliates. Third party registered and unregistered trademarks and logos are the property of their respective owners.

310125 REV E JE18