

DATA SHEET

OEM: 4009-231-A26


AFTERMARKET: N/A

HIGH FLOW FRESH WATER PUMPS

REVOLUTION 4009 SERIES

APPLICATIONS

Multi-fixture RV potable water installations. Other uses may include 24 VDC pressurized water systems in cabins. This pump may be used for general water transfer. For other applications, contact Pentair Shurflo.



CERTIFICATIONS AND STANDARDS

Revolution 4009 Series complies with the following certifications and standards:

- ◆ CE
- ♦ E-Mark
- ◆ KTW-BWGL
- RCM Mark
- ◆ NSF 372
- ◆ CSA Z240.3.2

SPECIFICATIONS

PUMP

◆ **Type**: 4 Chamber Diaphragm

◆ Ports: 1/2″-14 NPSM-Male

◆ **Liquid**: 130 °F [54 °C] Max

◆ **Prime**: 9 feet [2.7 M]

♦ Inlet PSI: 30 PSI[2.1 Bar] Max

♠ Run Dry: Yes

◆ Flow Rate: 3.0 GPM[11.4 LPM]

ELECTRICAL

◆ Motor: 24VDC Permanent Magnet, Intermittent Duty

Protection: Thermal Overload, Automatic Restart
 Leads: 16 AWG, 16" [40 cm] Red +, 13" [33 cm] Black

• Fuse: 5 Amp Time Delay Recommended

◆ Control: Adjustable Switch with Check Valve

Shut-Off: 40 PSI[2.8 Bar] ± 5 PSI[0.4 Bar] Restart: 30 PSI[2.1 Bar] ± 5 PSI[0.4 Bar]

MATERIALS

◆ Housing: Polypropylene

Valves: EPDMDiaphragm: TPE

◆ **Hardware:** Stainless Steel

◆ Baseplate: Metal

◆ **Type**: 4 Chamber Diaphragm


RELATED DOCUMENTS


• 911-1038 Installation and Operation Manual

DIMENSIONAL DATA

All dimensions are for reference only. Do not use to create specification control drawing.

4009-231-A26 MODEL





SHURflo reserves the right to update specifications, proices, or make substitutions.



SHURflo UK Customer Service Hypro EU Limited Unit 9, Bourn Quarter Caldecote, Cambridge CB237FW United Kingdom Shurflo.service@pentair.com

SHURflo European Customer Service Pentair Water Belgium BV Industriepark Wolfstee Toekomstlaan 30 B-2200 Herentals, Belguim Shurflo.service@pentair.com pentair.com