Simer.

JET PUMPS



MODELS 2210C, 2207C, 2205C

SHALLOW WELL JET PUMPS

MODEL 2210C 1 HP MODEL 2207C 3/4 HP MODEL 2205C 1/2 HP

- Reliable performance to depths of water 25' or less
- Rugged cast iron construciton maximizes pump life
- Heavy-duty dual-voltage motor 1/2 HP preset at 115 V; 3/4 HP and 1 HP are preset at 230V
- Pre-wired pressure switch preset for 30/50 PSI operation
- Self priming after pump housing is initially filled . Check valve or foot valve required.





PERFORMANCE

					Pressure Switch GPM Pumped at Different Depths to Water*					ater*	Pressure		
Model	HP	Warranty	Voltage	Amps	On	Off	0'	5'	10'	15'	20'	25'	Shut-off
2210C	1	1-year	115/230	12.0/6.0	30	50	21	20	18	16	13	9	70 PSI
2207C	3/4	1-year	115/230	11.0/5.5	30	50	19	16	14	13	11	7	67 PSI
2205C	1/2	1-year	115/230	8.5/4.2	30	50	8.5	7.5	6.5	6	5	3.5	65 PSI

*All performances shown in gallons per minute at 40 PSI (pound per square inch) discharge pressure at top of well.

ORDERING INFORMATION

Model	UPC	Carton (L x W x H)	Cube	Pallet Qty.	Weight
2210C	0 22315 36160 7	19" x 10.82" x 10.5"	1.249	24	53 lbs.
2207C	0 22315 36159 1	19" x 10.82" x 10.5"	1.249	24	45 lbs.
2205C	0 22315 36158 4	19" x 10.82" x 10.5"	1.249	24	38 lbs.