



SUMP PUMPS

MODELS 2161, 2163, 2164, 2165, 2166, 2168

ZINC WITH PLASTIC BASE SUMP PUMP

TETHERED MODELS

Operates in 14" basins or larger

- 2161 1/4 HP
- 2163 1/3 HP
- 2165 1/2 HP

VERTICAL MODELS

Operates in 10" basins or larger

- 2164 1/3 HP
- 2166 1/2 HP
- 2168 3/4 HP

Thermoplastic construction

Resists corrosion

Zinc motor housing

Dissipates heat quickly and extends motor life

Stainless steel fasteners and hardware


Superior quality

Smooth Flow Hydraulics™

Delivers high performance for demanding applications



Energy Efficient Design
Diseño Eficiente de la Energía
Conception rationnelle de l'énergie



PERFORMANCE (GPH)			DISCHARGE HEIGHT ABOVE PUMPING LEVEL					MAX. LIFT	FLOAT SWITCH		SOLIDS HANDLING
MODEL	HP	Warranty	0'	5'	10'	15'	20'		ON	OFF	
2161	1/4	1 Year	3,200	2,700	2,160	1,500	-	20'	14"	5"	3/16"
2163	1/3	1 Year	3,600	3,060	2,400	1,680	660	22'	14"	5"	3/16"
2164	1/3	1 Year	3,600	3,060	2,400	1,680	660	22'	7.5"	3"	3/16"
2165	1/2	1 Year	4,200	3,660	3,000	2,160	960	22'	14"	5"	3/16"
2166	1/2	1 Year	4,200	3,660	3,000	2,160	960	22'	7.5"	3"	3/16"
2168	3/4	1 Year	4,700	4,200	3,540	2,820	1,800	24'	7.5"	3"	3/16"

ORDERING INFORMATION				
MODEL	UPC	CARTON DIMENSIONS	PALLET QTY.	WEIGHT
2161	022315377738	8" x 6" x 12.75"	105	7.7 LBS.
2163	022315377745	8" x 6" x 12.75"	105	7.7 LBS.
2164	022315377752	8" x 6" x 12.75"	105	7.7 LBS.
2165	022315377769	8" x 6" x 12.75"	105	10 LBS.
2166	022315377776	8" x 6" x 12.75"	105	10 LBS.
2168	022315377783	8" x 6" x 12.75"	105	10 LBS.

Includes: 1 1/2" NPT discharge, 8' grounded power cord, piggyback-style switch for automatic or manual operation, detailed owner's manual
Check Valve replacement is recommended