




SHALLOW WELL JET PUMPS



MODEL 2802 3/4 HP
MODEL 2800 1/2 HP

- Reliable performance at 25' depth to water or less
- Ready to Install 115 volt motor
- Pressure switch pre-set to 30-50 PSI
- 1" NPT suction and discharge
- Excellent self-priming capability after pump housing is initially filled (Check or foot valve required)
- Maximum pumping capacity for 3/4 HP to 8 gallons per minute
- Maximum pumping capacity for 1/2 HP to 5.5 gallons per minute



PERFORMANCE

Model	HP	Warranty	Voltage	Amps	Pressure Switch		GPM Pumped at Different Depths to Water*					Pressure Shut-off
					On	Off	5'	10'	15'	20'	25'	
2802	3/4	1-year	115	8.6	30	50	7.8	7.3	6.7	6.1	5.0	74 PSI
2800	1/2	1-year	115	7.2	30	50	5.1	4.5	4.1	3.5	3.1	63 PSI

*All performances shown in gallons per minute at 40 PSI (pound per square inch) discharge pressure at top of well.

ORDERING INFORMATION

Model	UPC	Carton (L x W x H)	Cube	Pallet Qty.	Weight
2802	0 17561 91158 4	16" x 9.75" x 11"	3.383	18	27.1 lbs.
2800	0 17561 91107 2	16" x 9.75" x 11.5"	.97	18	23.55 lbs.